



Shenzhen Dayun Links Co.,LTD

Product specification

Model : LY-130XX2

write :

Audit:

Date : 2017-05-20

1: Appearance picture



2: Product Functions

- H.264, AVI compression format, synchronous real-time monitoring and high-definition video
- 960P real-time image transmission, adaptive network, up to 25/30 frames / sec smooth experience
- Echo cancellation and noise suppression technology, the perfect full-duplex voice effect
- Possess Granville Technology Grain-media Cloud P2P penetration technology, a key remote, plug and play
- Air-Join, a key initiative to set WIFI, step network, the ultimate simple
- Horizontal and vertical rotation, multi-faceted cruise
- Support multi-user remote preview

3: Product size chart



4: Technology Parameters

System	Host processor	Industrial embedded microcontroller FH8810
	Operating system	Embedded LINUX operating system
Video	Image Sensor	1.3MP CMOS
	Video compression	H.264、 AVI
	Video Standard	PAL、 NTSC
	Monitoring image quality	1280*960/640*480/320*180
	Video Quality	1280*960/640*480
	Image motion detection	support
	Min illumination	0.1LUX/F1.2
	Grab function	support
	Video Flip	support
Audio	Coding Standards	G.711/G.726
	Audio Input	support
	Audio output	support
Recording Management	Video mode	Manual Recording、 Motion detection recording、 Timer recording、 Alarm recording
	Recordings storage	TF card \ computer \ mobile phone
	Remote Playback、 download	support



Shenzhen Dayun Links Co.,LTD

	Alarm is triggered	Video Push、Speaker alarm、Alarm recording、grab、sending Email
Net	Wired Ethernet port	RJ-45 10-100MB auto Adapted Ethernet interface
	wireless network	802.11b/g/n
	Stream	Dual-streaming
	NIV	Support TCP/IP、RTSP、ONVIF etc.
	P2P networking	Smart P2P
	WIFI networking	Smart-link + sonic
Expend	IR-CUT	support
	Micro SD card	Maximum support 64GB TF card
	WIFI	support
	433MHz alarm	Not support
	Lens	3.6MM
powered by	power supply	DC 5V 2A
	power	5W
condition	Storage temperature	0°C - + 55°C
	Storage humidity	10% - 90%
others	Lens	3.6MM